

17th Day of Slovene Paper Industry
21. – 22.11.2013

Modernisation of a testliner production



BELLMER

Gegr. 1842

PAPER TECHNOLOGY

The following 25 minutes...

- ▶ Design finding & determination
- ▶ Sheet formation
- ▶ Runnability
- ▶ Energy saving
- ▶ Specific requirements



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Production data PM

Program:	Testliner, Fluting
Basis weight range	100 – 300 g/m²
Raw stock	100 % waste paper
Future max. production speed	max. 1.000 m/min @ 100 g/m²
Increase of production	30 - 60 % subject to grammage
Design speed	1,000 m/min for the new parts
Wire width	4,700 mm
Operating width of reeler	4,370 mm untrimmed
Production volume	227,000 t/a net

Main targets of the rebuild:

- ▶ Quality improvement
- ▶ Increase of production volume
- ▶ Flexible operation




BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Original machine configuration bottle necks




Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Original machine configuration bottle necks



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Design finding & determination

High demands on rebuilt PM:

- ▶ Sufficient dewatering capacity of wire sections upon keeping/improvement of quality
- ▶ Stable web running in pre-dryer section at high speed
- ▶ Fast transfer (ropeless system, pulper)
- ▶ High speed sizing with film press
- ▶ Evaporative capacity pre-dryer & post dryer sections has to be sufficient
- ▶ Suitability of existing components for new speed
- ▶ High reeling quality



BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Modernisation of a testliner production

- ▶ **Design finding & determination**
- ▶ **Sheet formation**
- ▶ **Runnability**
- ▶ **Energy saving**
- ▶ **Specific requirements**



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Machine configuration after rebuild, wire section



BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Situation of existing headbox before modernisation




Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Situation of existing headbox after modernisation



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Modernisation of a testliner production

- ▶ Design finding & determination
- ▶ Sheet formation
- ▶ Runnability
- ▶ Energy saving
- ▶ Specific requirements




Gegr. 1842

BELLMER

PAPER TECHNOLOGY

One-row dryer system TURBODrying™ with vacuum rolls



- ▶ One-row dryer section design
- ▶ Vacuum rolls instead of drying cylinders
- ▶ Minimum open draw and high web running stability




BELLMER

Gegr. 1842

PAPER TECHNOLOGY

New vacuum roll drilled rotating shell



- ▶ By special drilling geometry, open area is increased to 64%




BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Additional pre-dryer group



- ▶ Web stabilizers in the pre-dryer section
- ▶ Ropeless transfer




BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Ropeless tail threading BELLMER BLowFeed™



Gegr. 1842

BELLMER PAPER TECHNOLOGY

Machine configuration after rebuild, TURBORreeler™



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Extension of steam & condensate system




Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Complete new multi-motor drive



Gegr. 1842

BELLMER

PAPER TECHNOLOGY


New mechanical drive



Gegr. 1842

BELLMER PAPER TECHNOLOGY

Extension of PCS



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Machine configuration after rebuild, further components

- ▶ Extension of vacuum system including field piping
- ▶ > 100 new dry wire guide rolls
- ▶ Extension of central oil lubrication system



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Modernisation of a testliner production

- ▶ Design finding & determination
- ▶ Sheet formation
- ▶ Runnability
- ▶ Energy saving
- ▶ Specific requirements



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Machine configuration after modernisation with film press



New film press
TURBO*CombiFilmSizer*™




BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Size press operation for special products



new film press
TURBOCombiFilmSizer™




BELLMER

Gegr. 1842


PAPER TECHNOLOGY

Energy saving

Reduced steam consumption in post dryer section with TurboFilmSizer,
starch application 3-5 g/m² in total



TURBOCombiFilmSizer™ in operation



Gegr. 1842

BELLMER PAPER TECHNOLOGY

Machine configuration after rebuild, post dryer section



► New hood with strong insulation for high dew point



BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Machine configuration after rebuild, post dryer section



► New air technology



BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Machine configuration after rebuild, post dryer section



- ▶ Adapted air technology
- ▶ Water recovery (partly)



BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Modernisation of a testliner production

- ▶ Design finding and determination
- ▶ Sheet formation
- ▶ Runnability
- ▶ Energy saving
- ▶ Specific requirements



Gegr. 1842

BELLMER

PAPER TECHNOLOGY

Size press operation for special products

Special products require high penetration:

- Grade A
- Grade B
- Grade C

Basis weight 140 g/m²
Basis weight 190 g/m²
Basis weight 240 g/m²



BELLMER

Gegr. 1842

PAPER TECHNOLOGY

Starch preparation plant



BELLMER

Gegr. 1842

PAPER TECHNOLOGY